

Allegro 1120 Series Digital Video Surveillance Recorder



Quick and Easy VCR Replacement

- Rock-Solid industrial operating system
- Advanced Wavelet Compression
- Rapid Boot (only 5 Seconds)
- Record and playback multiplexed video
- 3 Selectable Video Quality Modes
- Built-In Date/Time Generator
- Simple On Screen Setup Menu
- Variable Speed Searching
- Quick Search by Date/Time or Alarm Log
- Remote Print Capture via PC on RS-232 port
- Remote programming and control via RS-232 port
- Variable recording speed up to 60 images per second
- Supports most major brand multiplexers*, all quads and matrix switchers... or just a single-camera
- Frame by frame viewing
- On Screen Display eases image searching
- Locking Front Panel**
- Schedule Recording for 7 Days**
- Alarm Event Recording**
- Alarm Index Recording**

*Contact JPI for current compatibility list.

120GB

Specifications

Video Standard

NTSC, 525 TV Lines, 60 Fields/Sec
PAL, 645 TV Lines, 50 Fields/Sec

Video Input/Output

Composite: 1.0 V p-p, 75 ohms, Unbalanced,
BNC Connectors

Resolution

NTSC/EIA: 720 x 486, PAL/CCIR: 720 x 576

3 Video Quality Modes

Super, High, Normal

Recording & Playback Speed

NTSC: 60P, 30P, 15P, 8P, 4P, 2P, 1P and 0.5P
PAL : 50P, 25P, 12P, 6P, 3P, 2P, 1P and 0.5P

High/Low Speed Search

2x, 4x, 8x, 12x, 16x/0.5P, 1P, 2P, 4P, 8P, 15P, 30P
Up to 600x fast reverse/forward

Quick Search

By Date/Time or Alarm Log

RS-232 Port

Remote Print with software
Remote Control of Front Panel Buttons

Date/Time Generator

On Screen Display

Battery Backed CMOS Real Time Clock

Operating Temperature / Humidity

41° to 104 °F / 80% or less

Storage Temperature

- 4° to 158 °F

Electrical Power Source

100~240 Volts, 50/60Hz

Dimensions

17.0"(W) x 12.0"(D) x 1.75"(H), 1U

*Specifications are subject to change without notice.



J P Industries
1693 Messina Drive
San Jose, CA 95132
Phone:(408) 929-4574
Fax:(408) 254-7764